

## TECHNICAL DATA SHEET

# **EPS® 2420**

Self crosslinking all-acrylic emulsion for joinery with an excellent balance of properties

#### **MARKET SEGMENTS**

Industrial Wood

#### **DESCRIPTION**

EPS<sup>®</sup> 2420 is a binder for interior and exterior wood applications such as multi-coat, enamels and varnishes with exceptional leveling properties and UV resistance. In-can transparency is a key feature of this product.

#### **PROPERTIES**

- Exceptional leveling
- Clear in-can
- Excellent block
- Exterior durability
- Medium hardness

- Good flexibility
- Good early water and water resistance
- Good stackability
- Low water uptake
- High transparency
- APE-free \*

# COMMON APPLICATIONS Topcoat

Specifications	
Weight Solids	45.0 +/- 1.0%
Viscosity, 23 °C	< 500
рН	7.3 - 8.3

### **Typical Properties**

Volume Solids	43.4 +/- 0.7%
Weight/Gallon	8.60 +/- 0.10 lbs.
MFFT	+5° C
Volatile(s)	Water, ammonia, propylene glycol (0.074%)

## **Suggested Coalescing Solvent(s)**

DPM	2.50%
DPnB	2.50%
Butyl Cellosolve	2.50%
Butyl Carbitol	2.50%

<sup>\*</sup> Made without APE-containing surfactants



Distributed by:
Ravago Chemicals North America
(833) RAV-CHEM
info@RavagoChem.com
www.RavagoChemicals.com

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com

7/14/2020

**TECHNICAL SUPPORT:** These guidelines are offered to assist the paint formulator in achieving the high performance properties noted and are offered for illustration purposes only; the paint formulator bears sole responsibility for the performance of the final coating product.

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epscca.com.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at https://www.epscca.com/galleries/pdfs/salesterms.pdf.